

DAIRON

**RotaDairon® Soil Renovator™
For Skid Steer Loader**

RDH 52

**Turn tough soil
into great turf**

RDH 60



Quality, since 1958

www.mge-dairon.com



Printed on recycled paper without any chlorine

One machine... One person... One pass™

RotaDairon® RDH 52 - RDH 60



What is the Compact Utility Loader RotaDairon® Soil Renovator™ ?

One of the main problems encountered when amenity areas (parks, private gardens and estates) and sports fields (golf courses) is fine cultivation of top soil before seeding. That is why The DAIRON Company, already world renowned for its tractor mounted Soil Renovators™ have developed a range of Skid-Steer Soil Renovators™ for all purposes : cultivation - grading - burying of stones, clods and overgrowth, grass + debris - seeding - rolling.

RotaDairon® Technical specifications

SOIL RENOVATOR™	RDH 52	RDH 60
Work width	52" (1300 mm)	60" (1500 mm)
Overall width	65" (1650 mm)	73" (1850 mm)
Adjustable work depth	5" 1/2 (140 mm)	
Rotor outside diameter	16" (400 mm)	
Depth control	Screw jacks system	
Grader blade adjustment	Mechanical	
Roller adjustment	Mechanical	
Number of blades	28	32
Number of screening rods	43	49
Mount	Quick Attach plate	
Transmission and safety	Hydraulic motor	
Weight (*)	1060 lbs. (480 kg)	1280 lbs. (580 kg)
Shipping dimensions	34" (850 mm) x 65" (1650 mm) x 67" (1700 mm)	34" (850 mm) x 73" (1850 mm) x 67" (1750 mm)
Seeder Box	SM 52 (SM 130)	SM 60 (SM 150)
Standard equipment	<ul style="list-style-type: none"> • Stainless steel • Windproof guarding • Seed gauge • Seed valve agitator • Fine seeding with dial seed valve 	
Distribution + seed rate adjustment (highly accurate)		
Hopper capacity Bushels (seeds volume) Litres	3 1/3 Bushels (100 litres)	5 Bushels (150 litres)
Weight	90 lbs. (40 kg)	100 lbs. (45 kg)

(*) with mesh roller • Specifications subject to change
• Patent US 5.236.060 - Canada 2.011.355 - France EBC 98 02 996



High tech hydraulic motor drive, oil bath chain drive, hydraulic.



Oversize 4 blades rotor, non glazing blades, unbreakable and unbendable screening rods.



RotaDairon® models available for tractors, skid-steer loaders and mini skid-steers.

Conditions of utilization

Utilization in overgrowth or on previously and deeply loosened soil cleared of big rocks.

e.mail : MGE@mge-dairon.com
www.mge-dairon.com



Skid Steer Loader Technical specifications

SKID STEER REQUIREMENTS	ROTADAIRON RDH 52	ROTADAIRON RDH 60
Required hydraulic	1500 to 3000 PSI (100 to 200 bar)	
Capacity (minimum)	12 GPM (48 l/min)	16 GPM (64 l/min)
Mount	Skid Steer w/Quick Attach	
Lift capacity	About 1,550 lbs. (700 kg)	

Your dealer

DAIRON S.A.

Les Hunaudières - D 92
72230 MULSANNE - FRANCE

Tel. : (33) 243 23 09 10
Fax : (33) 243 23 14 97



AN EXCEPTIONAL PROFITABILITY FOR US : QUALITY IS A MUST